

# Shrink Wrap Machine Store

Phone: 1-866-432-0042 / INT'L 1-718-859-0917 Fax: 718-228-7476 We Will Match Any Current Web Advertised Price!

## Preferred Pack PP3040-W Mid Volume Shrinkwrap L-Sealer

[http://www.shrinkwrapmachinestore.com/Mid\\_Volume\\_Shrinkwrap\\_Machine\\_188\\_12016.html](http://www.shrinkwrapmachinestore.com/Mid_Volume_Shrinkwrap_Machine_188_12016.html)



PRODUCT ID # : 12016

### PRODUCT SPECIFICATION

Max. Sealing Length	40 in.
Max. Sealing Width	30 in.
Max. Sealing Height	12 in.
Voltage	220 volts

### DIMENSIONS

Weight:	950.00 lbs.
Width:	41.00 inches
Length:	101.00 inches
Height:	43.00 inches

### OUR PRICE

LIST PRICE :	\$9500.00
INSTANT SAVING :	- \$653.00
SALES PRICE :	<b>\$8847.00</b>

### PRODUCT DESCRIPTION

Preferred Pack Mid Volume Shrinkwrap L Sealer PP3040 W Also Available with a W x L 30 x 50 Inch Seal Area We looked at the competition, and Preferred Pack was far ahead in Quality and Features. The Preferred Pack PP3040 W is a semi automatic wire seal L Sealer Shrinkwrapper that is perfect for midsize volumes. This Shrinkwrap Machine is a compact unit that can be transported from site to site. One person operation is simple and efficient. Simply move the package into the sealing area, over wrap and move product into the attached optional shrink tunnel. With a very generous 30 inch wide and 40 inch long work surface, the PP3040 W can accomodate very large products. Recommended Shrink Tunnel PP3610. Standard Series Semi automatic L Sealer with magnet clamping, powered takeaway conveyor, cylinder arm return, Teflon coated ceramic V groove beads, stainless steel compensator assembly, automatic cycle timing, pin perf, film clamps, casters. FEATURES Stainless Steel Film Clamps assure both sheets of film are flat on seal pad releasing all tension from seal ensuring a strong seal every time. Stainless Steel Compensator Assembly allows operator to adjust wire or micro knife temperature, unit compensates for residual heat in wire from previous cycle. Precise control of heat means consistent seal every cycle. Power Belted Product Discharge Conveyor automatically transfers product into shrink tunnel. Dual Magnetic Arm Hold Down Ensures positive even seal pressure to assure strong seal every time. Micro Knife Seal Blade Rugged Heavy Duty Frame Easy to Load Film Cradle with Brake Stainless Steel Film Clamps Smooth Seal Head Return with Cylinder Pin Perf. Hole Punch Power Belted Discharge Conveyor Dual Magnet Clamping Locking Casters Stainless Steel Compensator Assembly Teflon Coated Ceramic

Beads or Laminated Strip for Wire Sealer  
SPECIFICATIONS SEAL AREA WxL 30 x 40  
INCHES Machine Dimensions LxWxH 101 x 41  
x 43 INCHES Shipping Weight 950 Lbs. Power  
220 Volts, 30 Amps, Phase 1 Max. Film Width  
35 Inches WARRANTY Preferred Packaging  
Systems products are warranted to the original  
end user against defects in materials and  
workmanship from the date of purchase for a  
three 3 year period parts only included when  
used under normal operating conditions.

## PRODUCT FEATURES